

FARMALL COMPACT C SERIES II TRACTORS



# FARMALL<sup>®</sup> COMPACT C

SERIES II TRACTORS











# FARMALL COMPACT C SERIES II TRACTORS

4 Models | 35–55 HP | 28–47 PTO HP

BUYING A COMPACT TRACTOR DOESN'T MEAN SACRIFICING FEATURES FOR A COMPACT PRICE.

## PLENTY OF POWER.

The Farmall compact C deluxe series tractors feature Tier 4 B/Final-compliant and fuel efficient engines, ranging from 35–55 engine horsepower. A 3-point hitch with a lift capacity of up to 2,756 pounds is ready to handle the implements of your choice. The fully independent PTO with electro-hydraulic engagement allows for simple, no-effort engagement every time.

## A RANGE OF WAYS TO GET UP TO SPEED.

Farmall 35C and 40C offer a standard 12×12 gear transmission with synchronized shuttle, while the Farmall 45C and 55C offer a synchronized 16×16 gear transmission. All models offer a three-range hydrostatic transmission option, and mechanical front-wheel drive (MFD) gives you traction when you need it. When the going gets really tough, the differential-lock foot pedal locks both rear wheels together for additional traction.

## BUILT TOUGH.

The deluxe series stands out with heavier frames, wider track widths and longer wheelbases for increased stability, plus exceptional loader lift and rear hitch capacity. Because of their size, maneuverability and physical capabilities, they are go-to workhorses — whether moving mulch with a loader, mowing a lawn with a mid-mount mower deck, moving bales to the feedlot, blowing snow or digging with a backhoe.



# ALL WEATHER COMFORT & PRODUCTIVITY.

## WELCOME THE FARMALL COMPACT C CAB MODELS.

In a market with no shortage of options, the Farmall compact C deluxe series stands out with three of the roomiest cab models available—the 40C\*, 45C, and 55C. They offer the same deluxe features found in their non-cab counterparts, plus plenty more to help make your day more comfortable and productive, including:

- Easy entrance and exit on both sides
- Opening rear window for fresh air circulation and enhanced visibility
- A supportive, adjustable, cloth seat
- Wired for the radio of your choice
- 63 cu. ft. of interior space
- A comfort-creating HVAC system
- 47.9 sq. ft. of glass area for 360 degree views

## DELUXE FEATURES THAT WORK HARD.

- 1** Opening rear window, supported by gas struts, with lower viewing window for increased visibility to drawbar, three-point hitch and remotes.
- 2** Convenient, easy-to-use controls with loader joystick integrated into the right-hand console (hydrostatic layout shown).
- 3** Roomy floor space with suspended brake pedals (hydrostatic layout shown) and thick rubber floor mat that dampens sounds and vibrations.
- 4** HVAC controls conveniently located in the headliner, including 4-speed fan, heat, A/C and defrost/defog controls, plus 8 HVAC vents throughout the headliner.



The large operator area with deluxe features on Farmall compact C cab and non-cab tractors provides outstanding operator comfort along with greater ease of operation. (Gear transmission layout shown here.)

\* 40C offered in cab only





- A** Interior sun shade
  - B** Multiple rear view mirrors
  - C** Front windshield wiper and washer
  - D** Standard loader joystick built into console
  - E** Rubber floor mat
  - F** Tilting steering wheel
  - G** Easy-to-read digital dashboard and gauges
  - H** Suspended brake pedals
- Hydrostatic transmission controls layout shown here.



# ULTIMATE OPERATOR ENVIRONMENT.

Farmall compact C deluxe tractors—both cab and non-cab models—provide an exceptional operating experience in a simple, easy-to-use machine. The large, roomy platform makes it easy to access and exit, and the enhanced control layout quickly turns novice users into expert operators. Both versions come with a generous list of standard equipment and features, including\*:



\*Ask your dealer about other options and available features.

# A FULL LINE OF LOADERS, ATTACHMENTS AND IMPLEMENTS.

Choose from more than a dozen optional attachments that are quick and easy to switch out.



Model	Farmall 35C, 40C	Farmall 45C, 55C
Loader	L350A	L360A
Lift Capacity at Bucket Pivot Pin	2,000 lb. (907 kg)	2,500 lb. (1 134 kg)
Lift Capacity 19.7 in. (500 mm) from Bucket	1,540 lb. (699 kg)	1,830 lb. (830 kg)
Max Lift Height	105 in. (2 667 mm)	112.3 in. (2 852 mm)
Dump Angle at Full Height	58 degrees	49 degrees
Rollback Angle at Ground	30 degrees	39 degrees
Bucket	68 in. HD material bucket	72 in. HD material bucket

## CASE IH LOADERS ARE READY TO WORK FOR YOU.

A loader turns a tractor into a versatile, powerful workhorse. And loaders are very easy to install on Farmall compact C series deluxe tractors: just drive the tractor into the loader, put in the pins, attach the hydraulics and start working! Curved-boom loader arms let you easily see to the top of the bucket and around the front tires.

## QUICK AND EASY ATTACHMENTS AND IMPLEMENTS.

With a heavy-duty 3-point hitch, high-capacity responsive hydraulics and independent PTO, your Farmall C series deluxe tractor is ready for action.

- Side- and rear-discharge mowers (non-cab models only)
- Rear-mount finishing mower
- Front-mount rotary broom
- Rotary tiller
- Front-mount blade
- Front- and rear-mount snowblower
- Backhoe
- Rotary cutter
- Box blade
- Landscape rake
- Disk harrow
- Rear, 3-point mounted blade



# FARMALL COMPACT C SERIES II SPECIFICATIONS

MODEL	FARMALL 35C (NON-CAB)	FARMALL 40C (CAB)	FARMALL 45C (NON-CAB / CAB)	FARMALL 55C (NON-CAB / CAB)
<b>ENGINE</b>				
Type	Diesel, 3 cyl., 1.9 L (116 cu in.), turbocharged, Tier 4 B/Final			
Engine HP*	35	40	45	55
Air Cleaner	Replaceable dry element			
Fuel System	Electronically-controlled, indirect injection			
Fuel Capacity (Non-Cab / Cab)	10.5 gal. (40 L) non-cab only	12.4 gal. (47 L) cab only	10.5 gal. (40 L) / 12.4 gal. (47 L)	
Alternator	70 amp			
<b>PTO</b>				
PTO HP (Gear/Hydro)	29.7 / 28	34 / 32	38.2 / 36	46.7 / 44
PTO Speed	540 rpm			
PTO Type	Independent with electro-hydraulic engagement			
Mid-PTO Speed (Optional)	2,000 rpm			
<b>TRANSMISSION</b>				
Type (Standard/Optional)	12 × 12 shuttle shift / HST 3 range with cruise control		16 × 16 / HST 3 range with cruise control	
Maximum Forward Speed (Gear/Hydro)	14.2 mph (22.9 kph) / 14.8 mph (23.9 kph)		16.9 mph (27.3 kph) / 17.9 mph (28.7 kph)	
Gear / Shuttle Type	Synchro			
Rear Diff. Lock Engagement	Mechanical			
Brake Type	Wet multi-disc			
<b>HYDRAULIC SYSTEM</b>				
Pump Flow	8.2 gpm (31.0 L / min)			
Steering Pump Flow	Gear: 4.2 gpm (15.9 L / min) / HST: 5.3 gpm (20 L / min)			
Remote Valves	1	2	Optional: 1 (non-cab) or 2 (non-cab or cab)	
Type	Standard flex lower links and telescopic stabilizers			
3-Point Hitch	1			
Lift Capacity @ Ball End	1,808 lb. (820 kg)		2,756 lb. (1 250 kg)	
Lift Capacity @ 24 in. (61 cm) Behind Ball Ends	1,433 lb. (650 kg)		2,469 lb. (1 120 kg)	
<b>DIMENSIONS</b>				
Wheel Base (Non-Cab / Cab)	66 in. (168 cm)		73.2 in. (186 cm)	
Overall Width, with Standard Wheels / Tires	66.4 in. (169 cm)		69.1 in. (176 cm)	
Height to Top (Non-Cab / Cab)	93.5 in. (238 cm) to top of ROPS non-cab only	88.5 in. (225 cm) cab only	98.3 in. (250 cm) / 93.3 in. (237 cm)	
Weight (Non-Cab / Cab)	3,175 lb. (1 440 kg) non-cab only	3,803 lb. (1 725 kg) cab only	3,770 lb. (1 710 kg) / 4,453 lb. (2 020 kg)	

\*at 2,600 ERPM rated engine speed

SAFETY NEVER HURTS!™ Always read the Operator's Manual before operating any equipment. Inspect equipment before using it, and be sure it is operating properly. Follow the product safety signs, and use any safety features provided. CNH Industrial America LLC reserves the right to make improvements in design and changes in specifications at any time without notice and without incurring any obligation to install them on units previously sold. Specifications, descriptions and illustrative material herein are as accurate as known at time of publication, but are subject to change without notice. Availability of some models and equipment builds varies according to the country in which the equipment is used.

©2019 CNH Industrial America LLC. All rights reserved. Case IH is a trademark registered in the United States and many other countries, owned by or licensed to CNH Industrial N.V., its subsidiaries or affiliates. Any trademarks referred to herein, in association with goods and/or services of companies other than CNH Industrial America LLC, are the property of those respective companies. Printed in U.S.A. www.caseih.com CIH19051501

