



EXCEPTIONAL PERFORMANCE, INTEGRATED TECHNOLOGY, AGRONOMIC DESIGN

For decades, growers and custom applicators have trusted the Patriot® sprayer to take on tight application windows — but on today's operations, it takes more than timely, accurate spraying to drive profitability. You need complete vehicle control and a cab with built-in luxury — because comfortable operators are productive operators. And, you not only need connectivity and remote management capabilities to make better, data-driven decisions but also the ability to manage and coordinate your fleet from anywhere. Patriot 50 series sprayers deliver all that while building on the Agronomic Design™ principles Case IH sprayers are known for.





TAKE CONTROL OVER YOUR PRODUCT APPLICATION

In our industry, there's a lot that's out of our control — input costs, markets, Mother Nature. The Patriot 50 series sprayer is designed to help you expertly manage what you can control to maximize yield potential: crop protection and fertility applications. Plus, with a wide range of configurations and options, there's a model that fits your needs.





COMFORT & PERFORMANCE

- With a quiet, comfortable interior that boasts an abundance of glass for maximum, unrestricted visibility, a premium cab is designed to increase operator performance.
- Experience superior ride quality, stability and control with a 4-bar linkage chassis suspension system.
- The MultiControl Armrest layout provides exceptional ergonomics, with a comfortable operator seat that swivels 30 degrees to the right.

INTEGRATED TECHNOLOGY

- Connected solutions integrated into every Patriot 50 series sprayer provide endless opportunities for your operation.
- A suite of technology solutions which are capable of performing wireless file transfers, sharing guidance lines, creating prescription maps, fleet management, data sharing and product control.

AIM Command FLEX™ II advanced spray technology ensures consistent chemical
application rate, pressure and droplet size, with individual nozzle on/off control for
increased accuracy and efficiency.

AGRONOMIC DESIGN

- The proven **cab-forward**, **rear-engine design** helps you achieve timely application with optimized weight distribution, getting you into fields sooner with less compaction.
- **Strong, durable booms are built with robust material,** while the boom suspension design helps provide a stable platform for product application.
- Take accurate and effective coverage to the next level with the integrated AutoBoom® XRT
 Automatic Boom Height control option that detects and accommodates changes in terrain.
- A new center section design minimizes boom yaw in challenging conditions even with longer boom options.

NEW LOOK, SAME PATRIOT DNA

No matter how trusted and reliable, it's tough to teach an old sprayer new tricks. That's why we redesigned the Patriot 50 series sprayer from the ground up — while keeping the Agronomic Design features that mattered to you most. For decades, the distinctive cab-forward, rear-engine design and strong, durable boom have been critical to helping operators achieve accurate, timely spraying. And now, the Patriot sprayer combines those key elements with the most advanced technology to take high-efficiency spraying to the next level.

A ULTIMATE CONNECTIVITY

A suite of solutions and options to ensure machines are set up for the tasks at hand and tracking machines, jobs and field data.



CASE

B BOLD, NEW STYLING

With redesigned front and rear hoods, the look of the Patriot sprayer embodies all of what you expect from Case IH application equipment and technology: power, innovation and efficiency.





ONE PRODUCTIVE DUO

Connected solutions and options provide endless opportunities for your operation — whether you're running a single Patriot 50 series sprayer or a fleet of them. With the power of **AFS Connect™** and **Raven Slingshot®**, you have the unmatched connectivity, guidance, data and monitoring solutions you need to ensure your machines are ready for the tasks at hand.

COMPLETE VISIBILITY & CONTROL

 With two customizable displays — the AFS Pro 1200 and the Viper 4+ operators always have top-of-the-line vehicle and product control and the real estate to see what they want, when they want.

AFS PRO 1200 | MACHINE INTERFACE

Powered by AFS Vision Pro operating system, the AFS Pro 1200 provides precise control
over every aspect of the chassis from cab climate settings to exterior lighting controls, to
Bluetooth® and radio settings and even initiating the optional reversing engine fan operation.

VIPER 4+ | PRECISION FARMING

- With the Viper 4+ display, take precise application to the next level with product control and autoguidance solutions, including the industry-leading VSN® visual row guidance.
- VSN uses a non-contact stereo vision camera to navigate crop rows, so the operator can focus on all other aspects of application control.

FULL REMOTE VISIBILITY

- Remote Display Viewing. With the operator's permission, Case IH dealers and
 distributors as well as farm and operation managers can remotely see exactly what
 is on screen in the cab to assist with machine setup and optimization.
- Remote Service Support. There's no time for downtime. Now, you can work with your local Case IH dealer or distributor to remotely diagnose maintenance and service issues and to identify the parts you need.
- Remote Software Updates. Your local Case IH dealer or distributor can remotely push
 updates to your operating firmware wirelessly to take advantage of new features,
 functionality and enhancements.

VEHICLE HISTORY & MONITORING

- View and track every connected vehicle's path to and from the field to ensure uptime and productivity.
- Monitor sprayer progress across the field to improve tendering logistics.
- Vehicle tracking history and machine data can be referenced to identify equipment trends and enhance long-term productivity and efficiency.

GEOFENCING & CURFEWS

- Keep an eye on your fleet and receive notifications when equipment travels in or out of set boundaries.
- Set geofence boundaries to alert the tender truck operator when a sprayer is leaving the field so they're ready to refill.
- Add a machine curfew, so you're quickly alerted if a machine is operating after hours.







The Patriot 50 series sprayer offers two receiver options to best match your operation and allow fleet continuity. Here's what to consider when choosing between the RS1 autoguidance and AFS Vector Pro receiver:

RS1

- A fully scalable steering system that combines autosteer, GPS and Slingshot into one intuitive, easy-to-use option.
- Offers high-speed wireless connectivity, cellular-enabled technology and uninterrupted signals/data transfer.
- Utilizes WAAS and wireless RTK corrections and vehicle tracking.
- Includes five years of the Slingshot Gold subscription package.
- Compatible with VSN visual row guidance and the AutoTurn™ automated headland turning option.

AFS VECTOR PRO RECEIVER

- Equipped with the SC1 guidance option, the AFS Vector Pro receiver provides reliable and consistent terrain-compensated position and helps operators quickly acquire guidance lines.
- Streamlines guidance correction options, ranging from base (WAAS and AFS 1) to medium (AFS 2) to high (RTK and AFS RTK+) accuracy levels.
- Compatible with VSN visual guidance and the AutoTurn automated headland turning option.

VSN® VISUAL GUIDANCE SYSTEM

- VSN® visual guidance system helps to minimize crop damage and cover more acres in less time.
- Reduces operator fatigue allowing operators to increase the average length of their work day.
- Enhanced steering control and simple operation results in more acres covered in each available day.

YOU'RE IN CONTROL

With AFS Connect and Slingshot, included with the RS1 and SC1 guidance options, you can keep an eye on your fleet and operation — anytime, anywhere.

AFS CONNECT

- Every Patriot 50 series sprayer comes with an AFS Connect-compatible modem and a 5-year subscription from the factory.
- With an AFS Connect subscription, these features give you full visibility to your operation and maximize your uptime:
 - Data Visualization: View and store your application maps for full season-to-season recordkeeping and visualization.

- Prescription Tool: Create application prescriptions, then export and easily transfer to your Viper 4+.
- **Equipment Mode:** Toggle on and off machine location information to see your fleet when you need to.
- Vehicle Location History: Track machine location, parameters, and progress during jobs to better plan tasks like tendering logistics.
- Remote Display Viewing: View the AFS Pro 1200 from your desktop to coach operators on machine setup and operation.
- Remote Service: Connect with your dealer or distributor to update machine controllers and view detailed machine information.

SLINGSHOT

- Ensure your machines are set up for the tasks at hand.
 Plus, with a Slingshot mobile solution, easily view and monitor your vehicles from anywhere.
- With the Slingshot Gold subscription, included with RS1 and SC1 guidance options, these capabilities can maximize your operation's efficiency:
 - **Job Generator:** Set up jobs in the office and dispatch to the Viper 4+ in sprayers out in the field.
 - Job Sync: Share live coverage maps and guidance lines between two or more sprayers working in the same field.
 - Fleet View: Fleet or operations managers can see sprayer details in real time.
 - **Slingshot Link:** Enables over-the-air updates to the Viper 4+, RS1 and other hardware.
 - **File Transfer:** Allows for the transfer of data from sprayer to office and office to sprayer.
 - Remote Support: Remote, live viewing of the display in the sprayer to aid operators with setup or troubleshooting.





- Luxury leather, heated/ventilated seat with 30-degree swivel to the right
- B Carpet floor mat
- c Leather instructional seat
- More than 88 sq. ft. of glass for unrestricted visibility
- E Elevated foot rest
- **F** Leather-wrapped steering wheel
- G Telescoping steering wheel with memory lock

- H Digital instrument cluster display
- Viper 4+ display
- J AFS Pro 1200 display
- MultiFunction Handle
- Leather MultiControl Armrest
- M RAM Mount
- N Audio system
- Power ports





YOU'VE NEVER EXPERIENCED A CAB SO COMFORTABLE

Case IH engineers used years of research and customer input to design an operator environment so comfortable and quiet that operators won't mind those long days in the field. With a cab that perfectly blends simplicity, control and luxury, the Patriot sprayer puts productivity first.

- Speed presets
- Traction control
- Boom tilt up/down
- H Throttle controls
- Autosteer engage
- Customizable hot keys
- Center section raise/lower
- Tread adjust
- Speed scroll wheel
- K Auto-fold/unfold
- Forward-reverse propel quick shuttle

MULTIFUNCTION HANDLE

Redesigned and ergonomic MultiFunction Handle puts 95% of the commonly used controls at your fingertips.

CONTROL MADE SIMPLE

The same award-winning armrest design from current model Steiger and Magnum series tractors provides exceptional ergonomics and ease of use.



MULTICONTROL ARMREST

Attached to the operator seat, this armrest puts all controls and customizable hot buttons within reach.



EFFICIENT POWER, UNMATCHED PERFORMANCE

At the heart of every Patriot 50 series sprayer is an engine designed to deliver the power you need to work long days, economically cover thousands of acres and handle tough terrain. Case IH FPT engines use Selective Catalytic Reduction (SCR)-only emissions technology for extended maintenance intervals and enhanced fuel economy — helping you minimize operating costs.

BOOST TRAVEL SPEEDS

- We engineered the hydrostatic drive system to enable you to reach a wide range of speeds — and do so without the need to shift between ranges
- Increased transport speeds of up to 37 mph (Patriot 4350 and 4450 sprayers) help you get from field to field faster so you can cover more acres in a day.

- A spring-centered propel handle and speed scroll wheel help you reach your desired speed with ease.
- Integrated individual-wheel traction control enhances
 performance by automatically sensing wheel slip and
 regulating oil flow at each wheel motor to power through
 challenging conditions.

ROBUST DRIVETRAIN

- Drivetrain components are engineered to work as hard as you do.
- Infinitely variable hydrostatic pump and drive motors allow you to set your desired speed without the need to change ranges.
- Planetary hubs offer internal parking and service brakes.

- Forward/reverse quick shuttle makes changing direction of travel an easy process with the ability to set predetermined speed settings — all without having to move the MultiFunction Handle.
- Two speed preset selections are customizable to meet your specific needs.

REVERSING ENGINE FAN

 For operators in conditions with high amounts of field debris, a reversing engine fan option clears the grill screen and cooling cores — so you're always running under optimal conditions.

CRUISE THROUGH LONG DAYS WITH AN ULTRA-SMOOTH RIDE

We know comfortable operators are more productive operators. The Patriot 50 series sprayer delivers superior ride quality thanks to a 4-bar linkage chassis suspension system with 8 inches of total suspension travel. Best of all, it's designed for increased stability to keep you in control no matter what terrain you're working in.

SUPERIOR RIDE QUALITY

 Innovative 4-bar linkage chassis suspension system addresses both vertical and horizontal field loads with 8 inches of total suspension travel.

- Softer, air ride suspension paired with higher wheel travel provides unmatched shock absorption and load dampening.
- Tuned for Patriot 50 series sprayers, shock absorbers provide increased operator control during aggressive acceleration or braking and enhance ride quality and comfort during field operation.
- Rebound and jounce bumpers help limit component travel and dampen the casting loads, resulting in a softer ride over challenging terrain.

- Accessible grease banks make it easier to maintain your suspension system and keep it operating at peak performance.
- Effective suspension system shields help gently move plants away from suspension components to minimize crop contact.





DURABLE BOOMS MEET POWERFUL TECH

Every boom width on Patriot 50 series sprayers incorporates the same strong, advanced boom suspension design that operators have come to rely on. The parallel-link design packs superior strength without excessive weight and seamlessly incorporates boom technology options that take application accuracy and efficiency to the next level.

STRONG & STABLE

Built with robust materials, Patriot 50 series sprayer booms deliver a stable platform
for product application — even in the toughest conditions — through proven boom
suspension design. And when you're getting ready for transport, booms are automatically
locked when placed in the cradle, keeping them secure.

AUTOFOLD PLUS

Every boom option is equipped with an automated fold/unfold feature for maximum ease
of use — just push and hold the AutoFold Plus switch on the MultiControl Armrest and
the booms smoothly fold/unfold so you can get moving faster.

ACCUBOOM

- Operated through the Viper 4+ display, AccuBoom Automatic Boom Section control automatically turns off boom sections when the sprayer enters an area that has already been sprayed and then turns the sections back on when leaving the applied area.
- Customize overlap and section control to meet your desired field results and reduce overapplication to save on inputs.



AUTOBOOM XRT

- The integrated AutoBoom® XRT Automatic Boom Height control option detects and accommodates changes in terrain for more accurate and effective coverage across every inch of ground.
- Coupled with the innovative Patriot boom suspension design, AutoBoom XRT delivers solid boom control and stability.
- Radar sensors can be configured to detect the location of the ground or crop canopy to maintain a level spray platform and maximize boom life.





ADVANCED SPRAY TECHNOLOGY

With AIM Command FLEX II advanced spray technology, you get the best possible chance at maintaining your ideal chemical application rate, pressure and accuracy. This innovative technology is capable of higher flow rates and incorporates individual nozzle on/off control to ensure efficient, precise application — regardless of speed or terrain.

OPTIMIZE APPLICATION

- AIM Command FLEX II technology optimizes application rates and droplet sizes for consistent application, regardless of speed and ground conditions.
- With six modes of operation, this advanced spray technology delivers flexible and accurate application even in turns, rough terrain and irregular-shaped fields.

- Standard individual nozzle on/off control minimizes input costs and improves accuracy by reducing skips and overlaps.
- Enhanced nozzle control valves are higher-flowcapable, so you can spray at faster speeds or apply more product as needed, while severe-duty poppets help extend operating life.

HOW IT WORKS

 Pulse width modulation (PWM) spray technology ensures a constant application rate and spray pressure, even when sprayer speed changes. Think of it as a way to change nozzle tips without leaving the cab.

- Once you select a standard tip based on application rate, chemical droplet size and travel speed,
 AIM Command FLEX II technology automatically and precisely controls the flow to meet targeted application rates.
- Nozzle pulsing frequency is set at 20 times per second, but can be adjusted to either 10 or 15 Hz.
 Nozzle control valves vary the duty cycle to maintain the correct application rate as sprayer speed changes.

TURN COMPENSATION

- AIM Command FLEX II technology effectively compensates for different speeds across the boom to ensure correct application rates during turns.
- Each nozzle adjusts its duty cycle to match the targeted application rate based on speed, nozzle position on the boom and turn radius.

PRECISE PRODUCT FLOW

- AIM Command FLEX II technology provides individual nozzle on/off control, delivering the ultimate in spray accuracy and precision.
- The ability to control spraying at the individual-nozzle level helps reduce overapplication that adds costs and results in potential crop damage.
- To accommodate sprayer wheel tracks, fence rows or other field conditions, you can preset spray rates of approximately 50% higher or lower than your target rate on up to eight nozzles.

IMPROVED DRIFT CONTROL

- For on-demand drift control, AIM Command FLEX II technology allows you to toggle between three preset spray pressures that can be reset up or down at any time.
- Input a lower pressure setting to selectively avoid
 off-target application in sensitive areas or to respond
 to wind gusts. When normal conditions return, toggle
 back to the higher pressure setting on the go.
- You also have the option of inputting a higher pressure setting for greater canopy penetration.





BOOST YOUR APPLICATION POTENTIAL

Whether you're applying crop protection or fertility products, you can now drive productivity gains with maximum product flow capabilities — and maintain exceptional accuracy at any rate. Plus, a direct injection option allows operators to apply product to the entire field or selectively treat only certain portions based on pest pressure, helping you save on input costs and minimize waste.

WIDE RANGE OF FLOW CAPABILITIES

- With AIM Command FLEX II technology, nozzle control valves are capable of higher flow rates and increased operating pressure — so you can spray more product at faster speeds and maintain accuracy.
- Both low-flow and standard-rate product plumbing options are sized to match your application rate and speed requirements.
- For operators applying liquid fertilizer, take your effective spray range to a higher level with an **optional high-flow kit** that boosts your maximum flow rate to 269 GPM.

MATCH YOUR APPLICATION NEEDS

- Two product pump options include a standard cast iron housing or an optional stainless steel housing that helps enhance pump life when spraying corrosive and abrasive products.
- Factory-supplied, add-on nozzle body options can be installed offering enhanced flexibility and versatility to your spraying operation:
 - For increased product flow: Wilger Combo-Rate II nozzle bodies provide a larger inlet diameter.
 - For two-body spraying: Add another single-outlet end body when higher flow applications may be desired.
 - For even greater flexibility: Choose from two 5-way turret body options one version includes a radial lock design for all outlets, while another version provides three outlets with a square lug design and two with the radial lock design.



HAVE GREATER CONTROL WITH DIRECT INJECTION

- Optional direct injection simplifies cleanout, as only the injection tanks and boom
 plumbing are used to carry application products no tank mixing required. That
 means quicker product changeover and decreased risk of misapplication when
 changing products.
- Choose from **low- and high-flow pump options** to match your needs.
- **Save on input costs** by varying chemical application on the fly ideal for when you need to spot-spray areas with weeds.

CONVENIENT RINSE PROCESS

- Patriot 50 series sprayers are designed for **easy, efficient cleaning** to help maintain application accuracy and minimize cross-contamination of products.
- **Optional boom flush valves** allow you to rinse out each boom tube, without having to go through spray tips and nozzle bodies.
- **Optional automated rinse system** allows for tank-filling, tank-rinsing or boom-rinsing and can be controlled at the service center or from the cab with your Pro 1200 display.







KEEP ON ROLLING

With a range of tire options and axle adjust capabilities, it's never been easier to match your needs and keep working through the toughest conditions. Plus, advanced tire technology helps reduce compaction to enhance yield potential.

TIRE OPTIONS

- Tire options with IF or VF technology offer the advantage of lower inflation pressure to carry the sprayer's weight – which reduces compaction.
- Match your tires to your row spacing, field conditions and terrain with a range of options and sizes.

FENDERS & MUD FLAPS

- Durable, factory-installed fender options narrow or wide — are designed to match your tire selections.
- When you're operating in challenging, wet conditions, mud flaps can help keep your sprayer clear of debris a standard feature when you select wide fenders and optional with narrow fenders.

AXLE ADJUSTMENT OPTIONS

- Every Patriot 50 series sprayer provides the ability to hydraulically adjust track width to match your field conditions, terrain and row spacing.
- With the automated axle adjust option, just set your desired track width on the AFS Pro 1200 display and integrated sensors continually monitor the axle position to match.
- Further minimize compaction by setting front and rear axles at different widths, creating four sets of tracks.









TENDERING MADE EASY

Maximize time in the field and get tendering or maintenance out of the way quickly and efficiently. Everything is within reach with a one-stop service center, exclusive tip wash station, ground-level connections and an open architecture design.

ONE-STOP SERVICE CENTER

- With a **midship-mounted service center**, you can perform all primary tendering functions from one central location.
- Choose from **manual rinse or an automated rinse option** with a user-friendly display interface at the service center.
- A convenient remote reload station allows operators to activate
 the on-board product pump for suction filling and speed up the
 engine as needed, while a suction quick-fill option can help you
 speed up the process.



EASY-FILL OPTIONS

- The **optional fill flowmeter,** which can be positioned at either the service center or adjustable height front-fill location, monitors the volume of product added to the tank and automatically updates the tank level indicator on your Viper 4+ display.
- When you choose the adjustable front-fill option, an **air blowout feature** makes cleaning the fill hose a breeze, blowing remaining product into the product tank.

CONVENIENT WASH STATION

Mounted in the middle of the center section, an exclusive tip wash station
provides an easy, accessible way for operators to clean off spray tips with
both an air nozzle and water outlet.

MAXIMUM STORAGE

- An **exterior storage box** with two compartments comes standard, so you can store as many tools, PPE or maintenance items as you need.
- For even more storage space, another optional exterior storage box can be added when the direct injection option is not selected.
- An additional in-cab storage compartment is provided under the instructional seat, so you can pack up what you need and keep it out of the way while you're working.



SPRAY WITH CONFIDENCE

When time is of the essence, details matter. It's the smallest design elements, productivity-enhancing features, reliable technology and support networks that add up to deliver a high-efficiency operation. Agronomic Design is embedded in our DNA so you can apply the right amount of product at the right time — and every Patriot 50 series sprayer is backed by the best dealer and distributor networks in the business to keep you up and running.



5 WAYS THE PATRIOT 50 SERIES SPRAYER PUTS YOU IN CONTROL

- 1. **Get in fields faster:** The cab-forward, rear-engine design optimizes weight distribution with less compaction, while faster speeds and efficient tendering mean more time in the field and less time on the sidelines.
- Minimize variability: PWM spray technology automatically maintains droplet size and keeps application rates constant — reducing overapplication or underapplication and potential crop damage.
- 3. **Manage inputs:** AIM Command FLEX II advanced spray technology and individual nozzle on/off control reduces skips, overlaps and accommodates for turns.

- 4. **Maintain accuracy at your speed:** Drive according to ground conditions without sacrificing accurate coverage thanks to AIM Command FLEX II technology.
- Maximize uptime: Spray with confidence and achieve optimal return on your investment with exceptional support from the Case IH dealer and distributor network.

MODEL	PATRIOT 3250	PATRIOT 4350	PATRIOT 4450
CAB			
Cab Interior Space		132 cu. ft. (3.7 cu. m)	
Cab Glass Area	88.1 sq. ft. (7.5 sq. m)		
Cab Trim (Standard/Optional)	Deluxe / Luxury		
Operator Seat	Air suspension seat with adjustable 30 degree swivel to the right		
Operator Seat Adjustments	Lumbar support, firmness and auto weight adjustments, fore/aft and lateral isolators, back cushion tilt, swivel, fore/aft position, and height		
HVAC System	Automatic temperature control		
Cab Pressurization	Cab pressure mon	itored by HVAC system through the AFS Pro 1200, alerts displayed if cab pressure f	falls below 20 Pa
ENGINE	·		
Engine/Cylinders/Displacement	Case IH FPT Tier 4 B/Final, SCR / 6 cyl. / 6.7 L (409 cu. in.)	Case IH FPT Tier 4 B/Final, SC	CR / 6 cyl. / 8.7 L (531 cu. in.)
Engine HP	285 rated hp / 309 peak hp	335 rated hp / 374 peak hp	390 rated hp / 415 peak hp
Peak Torque	856 ftlb. (1 161 Nm)	1,143 ftlb. (1550 Nm)	1,258 ftlb. (1706 Nm)
Alternator	240 amp standard / 330 amp optional		
Fuel Tank/DEF Tank Capacity	150 gal. (568 L) / 21.5 gal. (81 L)		
CHASSIS			
Crop Clearance	53 in. (13	35 cm)	56 in. (142 cm)
Wheelbase	150 in. (381 cm)	160 in. (40	
Turning Radius	22.5 ft. (6.9 m)	25 ft. (7.6 m)	24 ft. (7.3 m)
Chassis Suspension	4-wheel independent, 4-bar linkage design, air ride with tuned shock absorber		
Total Suspension Travel	8 in. (203 mm)		
N/II TI Adirector and (Otton deed (Outine I)	$118-160$ in. ($2997-4064$ mm) $^{\circ}$; hydraulically adjusted from the cab with manual stops at 1-in. increments /		
Wheel Track Adjustment (Standard/Optional)	118—160 in. (2997—4064 mm)^; hydraulically adjusted from the cab; automatically adjusts to desired width entered into AFS Pro 1200 display. Adjustments can be made in ½-in. increments		
DRIVETRAIN			
Туре		Hydrostatic	
4-Wheel Drive	Full-time with traction control feature		
Shifting/Number of Ranges		Infinitely variable with two programmable speed pre-sets	
Speed Range(s)	0-32 mph (0-51.5 kph) 0-37 mph (0-59.5 kph)		
TIRES			
Row Crop Tire Selections	IF320/90R46, 380/90R46, VF380/90R46, LSW480/70R46	IF320/90R46, VF380/90R46, LSW480/70R46	VF380/105R50, VF420/95R50, VF480/80R50
Flotation Tire Selections	LSW680/	50R46	IF710/60R46, IF710/65R46
SOLUTION SYSTEM			
Solution Tank Fill Connection/Capacity	3 in. (76.2 mm) / 800 or 1,000 gal. (3028 or 3785 L)	3 in. (76.2 mm) / 1,200 gal. (4542 L)	3 in. (76.2 mm) / 1,600 gal. (6 057 L)
Solution Tank Material		Stainless steel	
Solution Tank Fill Location (Standard/Optional)		Service Center / Front Fill	
Rinse Tank Fill Connection/Capacity	2 in. (50.8 mm) / 100 gal. (379 L)	2 in. (50.8 mm) / 140 gal. (530 L)	2 in. (50.8 mm) / 160 gal. (606 L)
Rinse Tank Fill Location		Service Center	
OTHER TANKS AND CONTAINERS			
Product Pump (Standard/Optional)	$Hypro\ centrifugal\ pump,\ 2\times1\ \frac{1}{2}\ in.\ (50.8\times38.1\ mm),\ cast\ iron\ housing\ /\ Hypro\ centrifugal\ pump,\ 2\times1\ \frac{1}{2}\ in.\ (50.8\times38.1\ mm),\ stainless\ steel\ housing\ pump,\ pum$		
Low Flow/Standard Flow Rate Capacity	2.7 - 145 GPM / 5.8 - 240 GPM		
High Flow System	High flow kit flow capabilities of 8 - 269 GPM		
Fence Row Nozzles	Optional, Fixed 45 degree angle		
Foam Marker Option	3 gal. (11 L) soap concentrate tank, water supply from rinse tank		
BOOM			
BOOM	60/90 ft. (18.3/27.4 m), 60.	/100 ft. (18.3/30.5 m), 60/90/120 ft. (18.3/27.4/36.6 m), 66/132 ft. (20.1/40.2 m),	, 69/135 ft. (21.0/41.1 m)
BOOM Boom Length Selections	60/90 ft. (18.3/27.4 m), 60.	/100 ft. (18.3/30.5 m), 60/90/120 ft. (18.3/27.4/36.6 m), 66/132 ft. (20.1/40.2 m), Stainless steel spray bars	, 69/135 ft. (21.0/41.1 m)
BOOM Boom Length Selections Boom Plumbing Material			
BOOM Boom Length Selections Boom Plumbing Material Boom Nozzle Spacing	20 in. (508 mm): All boom options ex	Stainless steel spray bars	(5 section) and 120-ft. booms only
BOOM Boom Length Selections Boom Plumbing Material Boom Nozzle Spacing Boom Sections	20 in. (508 mm): All boom options ex 60/90 ft. (18.3/27.4 m): 5 or 6 section / 60/100	Stainless steel spray bars cept 132-ft. / 22 in. (559 mm): 132-ft. boom only / 20/30 in. (508 or 762 mm): 90-	(5 section) and 120-ft. booms only 0.2 m) and 69/135 ft. (21.0/41.1 m): 7 section
BOOM Boom Length Selections Boom Plumbing Material Boom Nozzle Spacing Boom Sections Boom Tip Breakaway Width	20 in. (508 mm): All boom options ex 60/90 ft. (18.3/27.4 m): 5 or 6 section / 60/100	Stainless steel spray bars cept 132-ft. / 22 in. (559 mm): 132-ft. boom only / 20/30 in. (508 or 762 mm): 90- ft. (18.3/30.5 m): 6 section / 60/90/120 ft. (18.3/27.4/36.6 m), 66/132 ft. (20.1/40	(5 section) and 120-ft. booms only 0.2 m) and 69/135 ft. (21.0/41.1 m): 7 section
BOOM Boom Length Selections Boom Plumbing Material Boom Nozzle Spacing Boom Sections Boom Tip Breakaway Width Boom Height Adjustment	20 in. (508 mm): All boom options ex 60/90 ft. (18.3/27.4 m): 5 or 6 section / 60/100	Stainless steel spray bars cept 132-ft. / 22 in. (559 mm): 132-ft. boom only / 20/30 in. (508 or 762 mm): 90- ft. (18.3/30.5 m): 6 section / 60/90/120 ft. (18.3/27.4/36.6 m), 66/132 ft. (20.1/40 m): 10 ft. 6 in. (3.2 m) / 60/90/120 ft. (18.3/27.4/36.6 m): 9 ft. (2.7 m) / 66/132 ft	(5 section) and 120-ft. booms only 0.2 m) and 69/135 ft. (21.0/41.1 m): 7 section
BOOM Boom Length Selections Boom Plumbing Material Boom Nozzle Spacing Boom Sections Boom Tip Breakaway Width Boom Height Adjustment OVERALL DIMENSIONS Total Weight	20 in. (508 mm): All boom options ex 60/90 ft. (18.3/27.4 m): 5 or 6 section / 60/100	Stainless steel spray bars cept 132-ft. / 22 in. (559 mm): 132-ft. boom only / 20/30 in. (508 or 762 mm): 90- ft. (18.3/30.5 m): 6 section / 60/90/120 ft. (18.3/27.4/36.6 m), 66/132 ft. (20.1/40 m): 10 ft. 6 in. (3.2 m) / 60/90/120 ft. (18.3/27.4/36.6 m): 9 ft. (2.7 m) / 66/132 ft	(5 section) and 120-ft. booms only 0.2 m) and 69/135 ft. (21.0/41.1 m): 7 section
BOOM Boom Length Selections Boom Plumbing Material Boom Nozzle Spacing Boom Sections Boom Tip Breakaway Width Boom Height Adjustment OVERALL DIMENSIONS	20 in. (508 mm): All boom options ex 60/90 ft. (18.3/27.4 m): 5 or 6 section / 60/100 60/90 ft. (18.3/27.4 m): 5 ft. 6 in. (1.7 m) / 60/100 ft. (18.3/30.5	Stainless steel spray bars cept 132-ft. / 22 in. (559 mm): 132-ft. boom only / 20/30 in. (508 or 762 mm): 90-ft. (18.3/30.5 m): 6 section / 60/90/120 ft. (18.3/27.4/36.6 m), 66/132 ft. (20.1/40 m): 10 ft. 6 in. (3.2 m) / 60/90/120 ft. (18.3/27.4/36.6 m): 9 ft. (2.7 m) / 66/132 ft 24-84 in. (610-2134 mm)	(5 section) and 120-ft. booms only 0.2 m) and 69/135 ft. (21.0/41.1 m): 7 section i. (20.1/40.2 m) and 69/135 ft. (21.0/41.1 m): 9 ft. 6 in. (2.9 m)

