



CASE IH LOADERS

TRACTOR/LOADER COMPATIBILITY

TRACTOR	LOADER	MAX. LIFT CAPACITY 31.5 in. (800 mm) Forward of Pivot Pin lb. (kg)		MAX. HEIGHT Under Level Bucket in. (mm)		BREAKOUT FORCE 31.5 in. (800 mm) Forward of Pivot Pin lb. (kg)	
		NSL ¹	MSL ²	NSL ¹	MSL ²	NSL ¹	MSL ²
FARMALL® COMPACT A SERIES							
35A 40A	L340A	890 (404) [†]		98 (2500)		1,900 (862) [†]	
FARMALL COMPACT C SERIES							
35C 40C	L350A	1,540 (699) [†]		105 (2667)		2,640 (1197) [†]	
45C 55C	L360A	1,830 (830) [†]		112 (2852)		3,114 (1412) [†]	
FARMALL UTILITY A SERIES							
50A 60A 70A	L545	1,742 (790)	2,205 (1000)	102 (2590)	106 (2680)	2,998 (1360)	3,131 (1420)
	L555	1,940 (880)	2,734 (1240)	105 (2670)		3,241 (1470)	3,527 (1600)
55A 65A 75A	L610 ⁴	1,828 (829)	3,153 (1430)	120 (3040)		N/A	
95A 105A 115A	L575	2,028 (920)	3,174 (1440)	134.5 (3416)		3,102 (1407)	3,372 (1530)
FARMALL UTILITY C SERIES							
65C 75C	L565	1,940 (880)	2,734 (1240)	105 (2670)		3,241 (1470)	3,527 (1600)
	L620	2,478 (1124)	3,179 (1442)	114 (2910)		3,739 (1696)	4,665 (2116)
90C 100C 110C 120C	L103	2,205 (1000)	3,241 (1470)	129 (3270)		3,175 (1440)	3,417 (1550)
	L575	2,028 (920)	3,175 (1440)	125 (3180)		3,351 (1520)	3,461 (1570)
	L620	2,478 (1124)	3,179 (1442)	114 (2910)		3,739 (1696)	4,665 (2116)
	L630	2,632 (1194)	3,428 (1555)	123 (3131)	124 (3149)	4,455 (2020)	5,661 (2567)
FARMALL UTILITY U SERIES							
110U 120U	L103	2,359 (1070)	3,461 (1570)	132 (3350)		3,395 (1540)	3,660 (1660)
FARMALL 100A SERIES							
110A 120A 130A 140A	L103 ³	2,094 (950)	N/A	133 (3370)	N/A	3,020 (1370)	N/A
	L104 ⁴	2,557 (1160)	3,814 (1730)	139 (3530)		3,682 (1670)	3,968 (1800)
VESTRUM® SERIES							
100 130	L103	2,381 (1080)	3,505 (1590)	143 (3640)		3,439 (1560)	3,682 (1670)
MAXXUM® SERIES							
115 125 135 145 150	L103 ³	2,381 (1080)	N/A	131 (3330)	N/A	3,439 (1560)	N/A
	L105 ⁴	2,932 (1330)	5,203 (2360)	150 (3810)		4,674 (2120)	5,975 (2710)
	L105 Long Reach ⁴	N/A	4,365 (1980)	N/A	156 (3950)	N/A	4,894 (2220)
PUMA® SERIES							
150 165	L106	3,594 (1630)	5,578 (2530)	154 (3920)		5,137 (2330)	6,415 (2910)
	L106 Long Reach	N/A	4,475 (2030)	N/A	166 (4220)	N/A	5,269 (2390)
185 200 220 240	L107	N/A	5,622 (2550)	N/A	168 (4270)	N/A	6,768 (3070)
	L107 Long Reach	N/A	4,519 (2050)	N/A	174 (4430)	N/A	5,490 (2490)
MAGNUM™ SERIES⁵							
180 200 220 240	L108	N/A	6,151 (2790)	N/A	162 (4110)	N/A	8,620 (3910)
250 280 310 340 380 400	L795	N/A	6,504 (2950)	N/A	183 (4640)	N/A	8,554 (3880)

¹ NSL – Non Self-leveling ² MSL – Mechanical Self-leveling ³ Only compatible with 2WD. ⁴ Only compatible with MFD. ⁵ The specs are the same for Magnum and AFS Connect™ Magnum.
[†] 19.7 in. (500mm) Forward of Pivot Pin Per ASABE (American Society of Agricultural and Biological Engineers) specifications.

SAFETY NEVER HURTS!™ Always read the Operators Manual before operating any equipment. Inspect equipment before using it, and be sure it is operating properly. Follow the product safety signs, and use any safety features provided. CNH Industrial America LLC reserves the right to make improvements in design and changes in specifications at any time without notice and without incurring any obligation to install them on units previously sold. Specifications, descriptions and illustrative material herein are as accurate as known at time of publication, but are subject to change without notice. Availability of some models and equipment builds varies according to the country in which the equipment is used.